MULTIPLE CD PLAYER

103CD/104CD/1050CD
DP-R797/R3090/R4090
SERVICE MANUAL

KENWOOD





In compliance with Federal Regulations, following are reproductions of labels on, or inside the product relating to laser product safety.

KENWOOD-Corp. certifies this equipment conforms to DHHS Regulations No. 21 CFR 1040. 10, Chapter 1, Subchapter J.

DANGER : Laser radiation when open and interlock defeated.
AVOID DIRECT EXPOSURE TO BEAM.

Illust is DP-R4090.

*** Refer to parts list on page 19.**

103CD/104CD/1050CD/DP-R797/R3090/R4090
BLOCK DIAGRAM



ADJUSTMENT

No.	ITEM	INPUT SETTINGS	OUTPUT SETTINGS	PLAYER SETTINGS	ALIGNMENT POINTS	ALIGN FOR	FIG.
Open the tray (Normal mode), then turn the power off.							
1	LASER POWER	–	Apply the sensor section of optical power meter on the pickup lens.	While pressing the TIME DISP. key, turn the AC ON. (Test mode) Press the PLAY/PAUSE key, then confirm that the display is "03".	–	On the power from 0.08 to 0.15 mW, when the diffraction grating is correctly aligned with the RF level of 1.0 Vp-p or more.	(a)
1. Press the STOP key. **2. Press the OPEN key.** **3. Load a disc, then press the CLOSE key.** **4. Press the PLAY key.** **5. Press the OPEN key to open the tray.** **6. Turn the power off. (Player stops as the tray is opened while the disc clamped.)** **7. While pressing the TIME DISP. key, turn the power ON to enter the Test mode.**							
2	TRACKING ERROR BALANCE	Test disc Type 4	Connect an oscilloscope as follows. CH1 : RF (CN2 pin 1) CH2 : TE1 (CN2 pin 6)	Press the PLAY/PAUSE key, then confirm that the display is "03".	TE BALANCE VR2	Symmetry between upper and lower patterns	(c)
3	FOCUS ERROR BALANCE	Test disc Type 4	Connect an oscilloscope as follows. CH1 : RF (CN2 pin 1) CH2 : TE1 (CN2 pin 6)	Press the PLAY/PAUSE key, then confirm that the display is "05".	FE BALANCE VR1	Optimum eye pattern	(b) or (d)
4	TRACKING GAIN	Test disc Type 4 Apply signal of 1.2 kHz, 50mVrms to CN2 pin 5-6.	Connect a LPF to CN2 pin 5-6 to which you connect an oscilloscope or AC voltmeters.	Press the PLAY/PAUSE key, then confirm that the display is "05".	TRACKING GAIN VR3	Two VTVMs should read the same value.	(e)

Note:
Type 4 disc : SONY YEDS-18 Test Disc or equivalent.
LPF: Around 47 kΩ+ 390 pF or so.
Step 1~4 are in Test Mode.

(a) Laser power



(e) Tracking gain



ADJUSTMENT

FIG.
(a)
(c)
(b) or (d)
(e)

FIG. (b)



- RF signal and TE signal in test mode (PLAY).
- If the diffraction grating has been adjusted correctly, the influence of triggering is observed on the TE waveform of approx. 18 μs from RF signal trigger point, in the form of a projection.

FIG. (c)



- RF signal and TE signal in test mode (Focusing servo ON / Tracking servo OFF). (Disc Type 4)
- Adjust TE signal so that the waveform is symmetrical in relation to VC. (TE BALANCE)

FIG. (d)



- RF signal in test mode (PLAY).
- Perform the tangential and focusing offset are focused into one point on the display. The crossing points above and below the center shall also be looked clearly.

  (FE BALANCE)

PC BOARD(Component side view)

CD player unit
X32-328X-XX

0-10 : 1050CD (K, P)
0-11 : 104CD (K, P)
0-12 : 103CD (K, P)
DP-R797 (K, P)





50CD (K, P)
04CD (K, P)
03CD (K, P)
P-R797 (K, P)

0-21 : 1050CD (Y)
0-22 : DP-R4090 (M)
104CD (Y)

0-23 : DP-R3090 (M)
103CD (Y)
DP-R797 (Y)

2-71 : DP-R4090 (E, T, X)
2-72 : DP-R3090 (E, T, X)



(c) Tracking error balance :
Symmetry between upper and lower patterns.

(b or d) Focus error balance :
Optimum eye pattern.



(e) Tracking gain :
Two VTVMs should read the same value.





Refer to the schematic diagram for the value of resistors and capacitors.

PC BOARD(Component side view)











Refer to the schematic diagram for the value of resistors and capacitors.



CAUTION: *For continued safety, replace safety critical components only with manufacturer's recommended parts (refer to parts list). ⚠ indicates safety critical components. For continued protection against risk of fire, replace only with same type and rating fuse(s). To reduce the risk of electric shock, leakage-current or resistance measurements shall be carried out (exposed parts are acceptably insulated from the supply circuit) before the appliance is returned to the customer.*

The DC voltage is an actual reading measured with a high impedance type voltmeter. The measurement value may vary depending on the measuring instruments used or on the product. Refer to the voltage dur ing PLAY unless otherwise specified; The value shown in ( ) is the voltage measured at the moment of STOP.

KAN03



CXD2507AQ*1



LA6541D

F G H I J



2SA1534A
2SA954
2SA992
2SC2878



2SC2785

DTA124ESA
DTC124ESA
UN4112
2SC1740S



UN4212
UN4219



2SD2012

NJM4565D



TA84

J K L M N O

1050CD
X32-328X-XX

DESTINATION		UNIT	A	B	C	IC3	IC6	D11	D23	S1	C99	R91, 97	E12	W122	W141	W187
COUNTRY	ABB.	No.														
U.S.A. CANADA	K P	0-10	YES	NO	YES	uPD78044FGF043	NO	YES	UZ-3.9BS8 or MTZJ3.9(B)	NO	NO	180	YES	YES	NO	YES	NO
PX	Y	0-21				uPD78044FGF023 or uPD78044FGF043	YES			YES				NO		NO	

104CD
X32-326X-XX

DESTINATION		UNIT	A	B	C	IC3	IC6	D11
COUNTRY	ABB.	No.						
U.S.A.	K	0-11	NO	YES	YES	uPD78044FGF023 or uPD78044FGF043	NO	NO
CANADA	P							
PX	Y	0-22					YES	
GENERAL MARKET	M							
AUSTRALIA	X	2-71						
U.K. EUROPE	T E							

IC10
D.R.I.V.E (DIGITAL FILTER) DAC
(BOTTOM VIEW)

IC5
1bit DAC
(BOTTOM VIEW)

*IC3
u-COM
(BOTTOM VIEW)

*IC6
IC PROTECT

IC11 (1/2)
IC12 (1/2)
IC11 (2/2)
IC12 (2/2)
20KHz LPF

MUTE CONT

FL DRIVE

DIGITAL

TA8409S



NJM4580D

TC9293AF



CXA1782BQ*1



ICP-N20





1050CD/104CD/103CD(K) (1/2)

103CD/104CD/1050CD/DP-R797/R3090/R4090

Y22-4870-10

KENWOOD



1050CD/104CD/103CD(K) (2/2)

CAUTION: *For continued safety, replace safety critical components only with manufacturer's recommended parts (refer to parts list). ⚠ indicates safety critical components. For continued protection against risk of fire, replace only with same type and rating fuse(s). To reduce the risk of electric shock, leakage-current or resistance measurements shall be carried out (exposed parts are acceptably insulated from the supply circuit) before the appliance is returned to the customer.*

The DC voltage is an actual reading measured with a high impedance type voltmeter. The measurement value may vary depending on the measuring instruments used or on the product. Refer to the voltage dur ing PLAY unless otherwise specified; The value shown in ( ) is the voltage measured at the moment of STOP.

EXPLODED VIEW (UNIT)



Parts with the exploded numbers larger than 700 are not supplied.

EXPLODED VIEW (MECHANISM)



AA	ø 3x8	:	N09-1522-05
AB	ø 2.6x8	:	N82-2608-46
AC	ø 2.6x10	:	N89-2610-46
AE	ø 3x10	:	N89-3010-46
AG	ø 2.6x6	:	N83-2606-46
AJ	WASHER	:	N19-0891-04
AQ	WASHER	:	N19-1435-05
AR	ø 2x3	:	N30-2003-46
AS	ø 2.6x6	:	N32-0260-46
AT	ø 2x5	:	N86-2005-46

CDM-25

Parts with the exploded numbers larger than 700 are not supplied.

103CD/104CD/1050CD/DP-R797/R3090/R4090

SPECIFICATIONS

[Format]

System .....Compact disc digital audio system
Laser.....Semiconductor laser

[D/A Convertors]

D/A Conversion 1Bit
Oversampling .....8 fs (352.8 kHz)

[Audio]

Frequency response.....4 Hz ~ 20 kHz, ± 0.5 dB
Signal to noise ratio.....More than 95 dB
Dynamic range .....More than 95 dB
Total harmonic distortion +noise
.....Less than 0.008 % (at 1 kHz)
Wow & flutter .....Unmeasurable Limit
Output level / impedance
Fixed (DP-R3090) .....2.0 V / 0.8 kΩ
Variable (DP-R4090).....(max.) 2.0 V / 0.8 kΩ
Headphone output (max.)
(DP-R4090 only) .....20 mW (32 Ω)

[General]

Power consumption.....13 W
Dimensions.....W : 440 mm (17-5/16")
H : 125 mm (4-15/16")
D : 397 mm (15-5/8")
Weight (Net) .....5.0 kg (11.0 lb)

Note :
We follows a policy of continuous advancements in development. For this reason specifications may be changed without notice.

Note:
Component and circuitry are subject to modification to insure best operation under differing local conditions. This manual is based on Europe (E) standard, and provides information on regional circuit modification through use of alternate schematic diagrams, and information on regional component variations through use of parts list.

KENWOOD CORPORATION
14-6,Dogenzaka 1-chome, Shibuya-ku, Tokyo, 150 Japan

KENWOOD SERVICE CORPORATION
P.O BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745, U.S.A.

KENWOOD ELECTRONICS CANADA INC.
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8

KENWOOD ELECTRONICS LATIN AMERICA S.A.
P.O BOX 55-2791, Piso 6 plaza Chase, Cl. 47 y Aquilino de la Guardia Panama, Republic de Panama

KENWOOD ELECTRONICS U.K. LIMITED
KENWOOD House, Dwight Road, Watford, Herts., WD1 8EB., United Kingdom

KENWOOD ELECTRONICS BENELUX N.V.
Meachelsesteenweg 418, B-1930 Zaventem, Belgium

KENWOOD ELECTRONICS DEUTSCHLAND GMBH
Rembrücker Str. 15, 63150 Heusenstamm, Germany

KENWOOD ELECTRONICS FRANCE S.A.
13 Boulevard Ney, 75018 Paris, France

KENWOOD ELECTRONICS ITALIA S.p.A.
Via G. Sirtori, 7/9 20129, Milano, Italy

KENWOOD IBÉRICA S.A.
Bolivia, 239-08020 Barcelona, Spain

KENWOOD ELECTRONICS AUSTRALIA PTY. LTD.
(A.C.N. 001499 074)
P.O Box 504, 8 Figtree Drive, Australia Centre, Homebush, N.S.W. 2140, Australia

KENWOOD & LEE ELECTRONICS, LTD.
Unit 3712-3724, Level 37, Tower 1, Metroplaza, 223 Hing Fong Road, Kwai Fong N.T., Hong Kong

KENWOOD ELECTRONICS GULF FZE
P.O.Box 61318, Jebel Ali, Dubai, U.A.E.

KENWOOD ELECTRONICS SINGAPORE PTE LTD.
No. 1 Genting Lane #02-02, KENWOOD Building, Singapore, 349544

KENWOOD ELECTRONICS (MALAYSIA) SDN BHD.
#4.01 Level 4, Wisma Academy Lot 4A, Jalan 19/1 46300 Petaling Jaya Selangor Darul Ehsan Malaysia